
HYDROTOOLS"

#52000

Solar Reel System For Above Ground Pools

Assembly Instructions

- Congratulations on your purchase of our Swimline Hydrotools Solar Reel System for Above Ground Pools. Please follow the instructions carefully so as to not void your warranty.
- 2. Please use your solar blanket and reel assembly in the manner it was intended for:
 - a. Your solar blanket is not a safety cover
 - b. Remove the solar blanket and Solar Reel assembly from the pool completely before swimming use.
 - c. Do not store the solar blanket on the ground in direct sunlight, as it will burn the lawn
- 3. Preparation & Assembly: Check inventory of all items and assemble as illustrated below. Read all instructions prior to assembly!



Part #54000 3" Tube Kit Fits pools 16'-21' in width

- (2) 94.75" x 3.0625" Diameter extruded metal shaft
- (1) 94.75" x 3.1875" Diameter extruded metal shaft
- (4) Through Bolts (1) Drill Bit
- (2) 24" Storage Straps
- (2) Wood Screw Storage Hooks


Part #54024 3" Tube Kit Fits pools to 24' in width

- (2) 105.75" x 3.0625" Diameter extruded metal shaft
- (1) 105.75" x 3.1875" Diameter extruded metal shaft
- (4) Through Bolts (1) Drill Bit
- (2) 24" Storage Straps
- (2) Wood Screw Storage Hooks

5. Positioning Your Solar Reel:

For Rectangular pools, place top-rail brackets at either end of pool. Secure each bracket with 6 SS screws supplied. For Oval pools, place top-rail brackets at either end of pool where radius begins. Secure each bracket as above.

For Round pools, place top-rail brackets at center of pool. Secure each bracket as above. See Figure A next page.




6. Trimming Your Solar Blanket:

• Lay your Solar Blanket (not provided) on top of water, bubble side down. IMPORTANT! Oval & Round Pool owners will need to fold their solar covers at point of placement of Reel Stands! The cover will unroll left and right of brackets & cross pole. Please allow 6 inches more material on length to allow for a fold where straps will be attached for wind onto reel system. (See Fig A above and Fig D below) With scissors trim blanket to fit shape of pool. Be sure to clear the inside top rail of pool.

7. ASSEMBLING The Reel System & Tube Kit:

- . Insert 2 small Rollers & Axels into the recepticals in each of the 2 Support Brackets.
- Place Solar Blanket Reel Stand & Support Brackets at either side of the pool.
- Assemble (2) Crank handles to (2) Roller Hubs using (2) Bolts supplied. (Internal Gear Teeth face inward to drive Tube Poles) and place into Reel Stand as shown below.
- Loosely assemble extruded tubes together. Slide excess width into adjoining tubes, dividing it up as equally as possible.
 Note: You must have a minimum of 9" of overlap in each tube!
- . Measure the width across the pool from back of roller hub to back of roller hub & adjust length of the tube assembly to fit the span.
- With tubes on flat surface, to ensure that poles are straight, secure each tube with 1-1"x1.5" hex head screw in each adjoining tube.
- Slide tubes into hubs & secure with one 1.5" screw for each hub. When fit and span is correct, secure the Reel Stands
 to the pool top rail using the stand brackets and 3 x 1" screws per each 2 piece bracket assembly.



Come in 6 inches from each tube end and attach a strap to the metal tube assembly. Use the hex head screws in the tube notch to attach the strap. Take the remaining 3 straps and connect them evenly along the length of the tube assembly. Use remaining hex head screws to additionally fix tubes together, spacing evenly. (See Figure B Above)

